


Hook-Up Wire

UL 1061

Construction



Product Description

1. Solid or stranded, tinned or bare copper conductor 30-16AWG
2. Color-coded semi-rigid PVC insulation
3. Rated temperature : 80°C
4. Rated voltage : 300V
5. Uniform thickness of wire to ensure easy stripping and cutting
6. Pass UL VW-1 & CSA FT1 vertical flame test
7. RoHS complaint

Application:

Internal wiring of computers, office, equipment and other electronic and electrical equipment

Ordering No.	Conductor			Insulation Thickness mm	Overall Diameter mm
	Type	AWG	No./mm		
ICA4000	Stranded	30	7/0.102	0.25	0.80
ICB4000		28	7/0.127		0.90
ICC4000		26	7/0.160		1.00
ICD4000		24	7/0.203		1.10
ICE6000		22	7/0.254		1.30
ICF6000		20	7/0.320		1.50
ICG6000		18	16/0.254		1.70
ICH2000		16	26/0.254		2.00
ICA7000		Solid	30		1/0.254
ICB7000	28		1/0.320		0.83
ICC7000	26		1/0.404		0.90
ICD7000	24		1/0.511		1.02
ICE9000	22		1/0.643		1.15
ICF9000	20		1/0.813		1.32
ICG9200	18		1/1.024		1.52
ICH8000	16		1/1.290		1.80